

MERIT MARQUIS[®] SERIES STOPCOCKS



SHERLOCK[®]
CONNECTORS

AIRLESS ROTATORS

CLEAR INNER LUMEN

SHARKS FIN HANDLE



Merit Medical

Marquis® Series Stopcocks



S1SNC — Standard pressure, one-way with swivel nut connector

M1SNC — Medium pressure, one-way with swivel nut connector

H1FLC — High pressure, one-way with fixed luer connector

H1RC — High pressure, one-way with rotating connector

S3SNC — Standard pressure, three-way with swivel nut connector

S4SNC — Standard pressure, four-way with swivel nut connector

M3SNC — Medium pressure, three-way with swivel nut connector

H3SNC — High pressure, three-way with swivel nut connector

M3RRC — Medium pressure, three-way with right rotating connector

H3RRC — High pressure, three-way with right rotating connector

Other configurations are available, ask your customer service representative.

S3FLC — Standard pressure, three-way with fixed luer connector

S4FLC — Standard pressure, four-way with fixed luer connector

M3FLC — Medium pressure, three-way with fixed luer connector

H3FLC — High pressure, three-way with fixed luer connector

L3SNC — Large bore, low pressure, three-way with swivel nut connector

L4SNC — Large bore, low pressure, four-way with swivel nut connector

The Marquis® Series Stopcock is another innovative accessory product from Merit. Our larger, easy-grip handle makes a Marquis Stopcock effortless to grip and turn. Our patented airless rotator prevents air bubbles while the Sherlock® Connector makes disconnection noticeably easier.

Using the same state-of-the-art design that made Merit's Manifold the industry standard, the Marquis Series Stopcock offers unsurpassed feel and ease-of-use. Available in pressure ratings of 200, 500 and 1050 PSI with the easiest turning handles on the market. Of course, the best test of any Marquis Stopcock is a direct comparison with any competing product. Once you've tried them all, you'll know why Marquis Series Stopcocks are truly "a cut above the rest."

TECHNICAL SPECIFICATIONS

Body Material:	Polycarbonate
Handle Material:	Delrin
Pressure Rating:	
Large bore:	50 PSI (3.45 BAR)
Standard:	200 PSI (13.8 BAR)
Medium:	500 PSI (34.5 BAR)
High:	1050 PSI (72.45 BAR)
Primary Handle I.D.	.079 inches (2.0 mm)
(Large bore)	.120 inches (2.5mm)
Packaging:	50 units per box, 4 boxes per case



Merit Medical Systems, Inc. ■ 1600 West Merit Parkway, ■ South Jordan, Utah 84095 ■ 1-801-253-1600 ■ 1-800-35-MERIT
 Merit Medical Europe ■ Horsterweg 24 ■ 6199 AC MAASTRICHT-AIRPORT ■ The Netherlands ■ +31 - 43 - 35 88 222
 Merit Medical Ireland Ltd. ■ Parkmore Business Park West ■ Galway, Ireland ■ +353 (0) 91 703 733
 Free phone from specific country:
Belgium 0800 72906 ■ **France** 0800 91 60 30 ■ **Germany** 0800 182 0871 ■ **Luxembourg** 0800 22522 ■ **Netherlands** 0800 022 8184 ■ **UK** 0800 973 115
 U.S. and Foreign Patents Pending.

www.merit.com

400177018/C ID 032502